

D. K. ENTERPRISE

201 SAI BHAWAN, MACHHLIPITH, SHAHPUR, SURAT - 395003 INDIA.
TEL /FAX : 0261-249 1514 MOBILE : 98241-25424
Web : www.dkenterprise.in E-mail : info@dkenterprise.in

HTR – D500

(A half tone resist discharge - printing agent)

HTR – D500 is especially designed to make a so called “High added value printed fabrics” by fading the ground colour of the fabrics. When you print it on padded fabrics with dyes or dyed fabrics, printed area will absorb and weaken the ground colour yield during steaming process. And as a result, you will be able to obtain a beautiful half tone discharge-printing effect on the fabrics. HTR – D500 is also applicable on the resist-printing process.

Properties :

Appearance : Light Yellowish Paste
pH : 6 – 9

Recipe of printing paste :

HTR – D500	50 - 100
CMC Soln.	50 - 0

	100 %

Process :

- A) Print HTR – D500 on the padded or dyed fabrics ---Dry---Steam (HP or HTS)
- B) Print HTR – D500---Dry---Overprinting dye paste---Dry---Steam (HP or HTS)
- HTR – D500 will offer better performance on wet-on wet resist - printing process i.e. process B).
 - HTR – D500 is most the most recommended to be used with Disperse or Acid dyes.
 - For reduction of viscosity, please dilute it with water.